

DXE1control

THE EFFICIENT MASTERPIECE

The DXE1*control* is the ultimate all-rounder for torque and angle bolting with an integrated documentation function. Based on the DXE1*docu*, it offers a comprehensive range of features for maximum versatility and efficiency.

With predefined bolting cases, automatic bolting and documentation of torque, rotation angle and preload force, this pump enables fast, safe and user-friendly work.



FOR THE OPERATION OF
HYDRAULIC WRENCHES
AND TENSIONERS



SMART

Data transfer to digital devices for seamless documentation




PRECISE

Rotation angle bolting (+/-2°) without additional sensor technology thanks to patented process



COMFORTABLE

Fully automatic bolting up to the preset hydraulic pressure with the push of a button



MODELS // DATA

Typ Type	Betriebsart Operation mode	Max. Betriebsdruck Max. pressure		Max. Durchfluss Max. flow		Motorleistung Motor power		Maße (L1 x B1 x H1) Dimensions (L1 x B1 x H1)	Gewicht Weight	
		bar	psi	l/min	gal/min	kW	hp		kg	lbs
DXE1 <i>control</i> 20	Automatik automatic	800 / 1.500	11,600 / 21,750	1,2	0.32	1,1	1.48	500 x 343 x 465 mm 19.68 x 13.50 x 18.30 in	40	88

Repeat accuracy: ≤ 4%, depending on the bolted joint. Technical data without guarantee.
Units available in the following voltages: 110V 50Hz, 110V 60Hz, 230V 50Hz, 230V 60Hz, 400V 50Hz, 400V 60Hz. Others on request.