HHC Hydraulic hoses

Durable but highly flexible thermoplast hydraulic hoses guarantee a very long life.

The 4-layer build-up includes 2 layers of high tensile steel fabric and robust fitting with 19 mm hexagon.

The volumetric expansion is very low. Hydraulic hoses model HHC are equipped with a male coupler half as standard.

Standard length are as per the chart below, further lengths or hoses with larger diameters are quoted on request.



Technical data HHC

Model	ArtNo.	Length	Operating pressure	Burst pressure	Connection 2 male coupler half CMY-1	Connection 1 thread nipple 3/8-NPT, outer	External diameter approx.	Bend radius min.	Width
		m	bar	bar			mm	mm	mm
HHC-5	N14200330	0.5	700	2.800			14	100	6.3
HHC-10	N14200300	1	700	2.800		N	14	100	6.3
HHC-20	N14200151	2	700	2.800	YELE:	2	14	100	6.3
HHC-30	N14200331	3	700	2.800			14	100	6.3
HHC-40	N14200152	4	700	2.800			14	100	6.3
HHC-60	N14200209	6	700	2.800			14	100	6.3
HHC-80	N14200313	8	700	2.800		and and a second	14	100	6.3
HHC-100	N14200332	10	700	2.800			14	100	6.3
HHC-120	N14200702	12	700	2.800	U U		14	100	6.3
HHC-150	N14200703	15	700	2.800			14	100	6.3

How to order

Hydraulic hose for all standard combinations (- pump - hose - cylinder -):

Order a standard hose with female coupler half HHC-... (e.g. HHC-20).

Hydraulic hose for coupling connections on both sides (both ends with CMY-1):

Order a complete coupler CCY-1 in addition to a standard hose HHC-... (recommended for long hydraulic hoses).

Hydraulic extension hose

(one male coupler half, one female coupler half):

Order a female coupler half CFY-2 (inner thread) in addition to a standard hose model HHC-...

Hydraulic hose without any coupler parts (both ends with threaded nipples):

Order model HH-... (both ends 3/8-NPT outer).