



HBD-ED Webbing sling, duplex construction, steel links on both ends

Made from polyester (PES), EN 1492-1 form Cr2, with capacity label.

Features

- Duplex construction, PU-starched, thermally fixed.
- With reeveable steel links.
- Woven tonnage stripes.
- Protection against hand injuries.
- Protection against cargo surface damage.
- Consistent pressure distribution onto pressure- and pull sensitive loads.
- UV-resistant, eliminating material ageing or embrittlement.
- Heat resistant up to +100°C.
- Moisture-resistant fabric, thus preventing frost damage (up to approx. -40°C).
- Low elongation (< 4 %).

INFO

HBD-ED - links are reeveable, webbing sling also applicable for use in choke hitch.

Technical data HBD-ED

Model	Colour code EN 1492	Capacity WLL, with one sling, straight pull kg	Capacity WLL, with one sling, choke hitch kg	Capacity WLL, with one sling, basket, angle β up to 7° kg	Capacity WLL, with one sling, basket, angle β 7°- 45° kg	Capacity WLL, with one sling, basket, angle β 45°- 60° kg	For webbing width mm	Link dimension HBD-ED b x d x t mm
HBD-01000-ED	violet	1000	800	2000	1400	1000	30	40 x 13 x 80
HBD-02000-ED	green	2000	1600	4000	2800	2000	60	75 x 16 x 125
HBD-03000-ED	yellow	3000	2400	6000	4200	3000	90	105 x 20 x 165
HBD-04000-ED	grey	4000	3200	8000	5600	4000	120	135 x 23 x 210

INFO

Other capacities upon request.