

ZGZB-KSP-PP Edge protector profile

Manufactured from polypropylene or recycled cardboard, to protect edges of loads. Length up to 6 m.



Technical data ZGZB-KSP-PP

Model	Art.-No.	Dimensions mm
ZGZB-KSP-PP	N39160004	190 x 190 x 20

ZGZB-ARM Slip restraining mats

Manufactured from compressed rubber granulate to achieve a defined friction coefficient of $\mu = 0.6$. Even if an emergency stop or evasive action is being taken – the cargo trucks or train wagons must not move. But only in very few cases the vehicle structure alone will offer sufficient load security.

For this reason, slip restraining devices should belong to the standard equipment of every professional transport. Slip restraining mats will decrease the danger which emanates from plain loading platforms. They will reduce the required total pre-tensioning forces during over top lashing of loads and will contribute – together with the textile lashings – that the loads will form a single unit with the vehicle or wagon.

The slip restraining effect will benefit especially those products, which do not stand a high surface pressure. The dangers resulting from incorrect load lashing practices are often underestimated. Acceleration forces in standard driving situations are close to the dead weight of the load.



INFO

The friction force FW of a slip restraining mat impedes load displacement and is physically explained as follows:

$FW = m \times G$
 $G = \text{Weight force}$
 $m = \text{Friction value}$

The difference between inertial force F and friction force FW is called securing force FS .

$FS = F - FW$

The securing force FS is the strength which has to be absorbed by the safety devices.

Technical data ZGZB-ARM

Model	Art.-No.	Dimensions mm
ZGZB-ARM-250-8	N39170001	1000 x 250 x 8