

Loading process lifting table HTPL

Special features

- Carrying loads 2000 – 6000 kg
- Lifting heights 1100 – 1600 mm
- Shearing in construction for evenly distributed loads
- Overrun capacity by reinforced platform (up to axle load 3 tons)
- Platform of bulb plate with maintenance hatch
- Reinforced basic frame
- Control in separate control cabinet including operating elements
- With upper, adjustable limit switch
- Individual adjustment for use outdoors
- Diverse accessories range

Technical Data

Model	Carrying load [kg]	Lifting height (H) [mm]	Platform (L x B) [mm]	Height (C) [mm]	Lifting time [sec.]	Motor output [kW]	Weight approx. [kg]
PL 20110-011	2000	1100	2250 x 1200	290	35	1.5	630
PL 20110-019	2000	1100	2000 x 1600	290	35	1.5	720
PL 20130-013	2000	1300	2500 x 1200	290	25	3.0	755
PL 20130-023	2000	1300	2500 x 1600	290	25	3.0	890
PL 20160-013	2000	1600	3000 x 1200	340	28	3.0	870
PL 20160-019	2000	1600	3000 x 1500	340	33	3.0	950
PL 20160-031	2000	1600	3000 x 2000	340	33	3.0	1150
PL 30110-007	3000	1100	2250 x 1200	320	25	3.0	860
PL 30110-017	3000	1100	2250 x 1600	320	25	3.0	910
PL 30130-015	3000	1300	2500 x 1400	320	30	3.0	880
PL 30130-035	3000	1300	2500 x 2000	320	30	3.0	1110
PL 30160-011	3000	1600	3000 x 1400	320	40	3.0	1115
PL 30160-049	3000	1600	3200 x 2400	320	40	3.0	1560
PL 50140-005	5000	1400	2200 x 1250	380	30	5.5	1047
PL 50140-021	5000	1400	2500 x 1600	380	30	5.5	1305
PL 60160-007	6000	1600	3000 x 1250	460	40	5.5	1470
PL 60180-013	6000	1600	3000 x 1500	460	40	5.5	1540
PL 60180-030	6000	1600	3000 x 2000	460	40	5.5	1790
PL 60180-045	6000	1600	3500 x 2400	460	40	5.5	2170

Further options, e.g. higher lifting loads, other platform sizes on request.
Optionally with reinforced platform for axle loads up to 10 tons.

