

### HT 08 M

Mobile elevating work bench with  
- manual-hydraulic lift

### HT 08 E

Mobile elevating work bench with  
- electric-hydraulic lift

Capacity 800 kg,

Platform height max. 1475 mm

For lifting and transporting of heavy loads in manufacturing and assembly processes.

#### Features

- TRIPLEX mast for lifting heights up to 1475 mm.
- Ergonomic handlebar for easy operation.
- Double-acting hand pump with increased lift per handle stroke (HT 08 M).
- Electric hydraulic unit with battery for comfortable and easy lifting (HT 08 E).
- Steering roller with brake for safe parking of the hand stacker.
- Robust construction with hard chromium plated piston.

#### Scope of delivery HT 08 E

- Battery and integrated battery charger.



#### Technical data HT 08 M and HT 08 E

Model	HT 08 M	HT 08 E
Art.-No.	N24380120	N24380129
Capacity, kg	800	800
Platform height max. h3+h13, mm	1475	1475
Platform height min. h13, mm	700	700
Stroke h3, mm	775	775
Overall length L1, mm	980	980
Platform length P1, mm	800	800
Platform width P2, mm	750	750
Tyre type <sup>1</sup>	PUR/PUR	PUR/PUR
Brake	manual	manual
Lifting height per pump stroke, mm	12.5	-
Lifting speed with/without load, m/s	-	0.08/0.125
Hoist motor rating, kW	-	0.8
Battery voltage, capacity, V/Ah	-	12/100
Battery charger, V/A	-	12/10
Weight, kg	134	152
Battery weight, kg	-	25

<sup>1</sup>PUR... Polyurethane

