

ASH Weld-on hooks

Capacity 1000 - 8000 kg

Weld-on hooks model ASH are universal attachments for use on trucks, excavators, low loaders and spreader beams, etc. The forged safety latch has high lateral stability and an ergonomic shape. Every weld-on hook has an identification number so that its history can be traced back through forging to the origin of the material.

The hook can be welded without any special preparation, e.g. prewarming.

The hook and safety latch are epoxy resin coated for added corrosion protection, the return spring is made from stainless steel.



Technical data ASH

| Model | ArtNo. | Capacity kg | Weight kg |
|-------|-----------|----------------|--------------|
| ASH 1 | N41000104 | 1000 | 0.5 |
| ASH 3 | N41000035 | 3000 | 1.3 |
| ASH 5 | N41000036 | 5000 | 2.4 |
| ASH 8 | N41000037 | 8000 | 3.6 |

Dimensions ASH

| Model | ASH 1 | ASH 3 | ASH 5 | ASH 8 |
|--------------------|---------|----------|----------|----------|
| Seam density a, mm | 4 | 6 | 7 | 8 - 9 |
| L1 x B1, mm | 90 x 25 | 130 x 35 | 160 x 45 | 170 x 50 |
| B2, mm | 19 | 26 | 30 | 40 |
| C, mm | 24 | 32 | 40 | 51 |
| H1, mm | 6 | 10 | 12 | 12 |
| H2, mm | 76 | 117 | 121 | 142 |
| L2, mm | 22 | 29 | 47 | 52 |

