



HSE Endless flat webbing sling, single ply

Made from polyester (PES), EN 1492-1 form A2, with capacity label.

Features

- Single ply, PU-starched, thermally fixed.
- Colour coded webbing.
- Woven tonnage stripes.
- Low weight allows easy handling.
- Protection against hand injuries.
- Protection against cargo surface damage.
- Consistent pressure distribution onto pressure- and pull sensitive loads.
- UV-resistant, eliminating material ageing or embrittlement.
- Heat resistant up to +100°C.
- Moisture-resistant fabric, thus preventing frost damage (up to approx. -40°C).
- Low elongation (< 4 %).

Technical data HSE

Model	Colour code EN 1492	Capacity WLL, with one sling, straight pull kg	Capacity WLL, with one sling, choke hitch kg	Capacity WLL, with one sling, basket, angle β up to 7° kg	Capacity WLL, with one sling, basket, angle β 7° - 45° kg	Capacity WLL, with one sling, basket, angle β 45° - 60° kg	Webbing width mm	Shortest possible length mm
HSE-01000	violet	1000	800	2000	1400	1000	30	500
HSE-02000	green	2000	1600	4000	2800	2000	60	500
HSE-03000	yellow	3000	2400	6000	4200	3000	90	500

INFO

Further capacities (up to 20t) and special lengths available on request.