



RSD

Round sling with duplex sleeve

Made from polyester (PES), EN 1492-2 with double stitch-less protection sleeve, with capacity label.

Features

- With double protection sleeve, PU-starched, thermally fixed.
- Colour coding of the protective sleeve.
- Printed-on capacities.
- Woven tonnage stripes, per ton capacity 1 stripe.
- Low weight allows easy handling.
- Protection against hand injuries.
- Protection against cargo surface damage.
- Highly flexible and adaptable to given shapes.
- UV-resistant, eliminating material ageing or embrittlement.
- Heat resistant up to +100°C.
- Moisture-resistant fabric, thus preventing frost damage (up to approx. -40°C).

Technical data RSD

Model	Colour code EN 1492	Capacity WLL, with one sling, straight pull kg	Capacity WLL, with one sling, choke hitch kg	Capacity WLL, with one sling, basket, angle β up to 7° kg	Capacity WLL, with one sling, basket, angle β 7°- 45° kg	Capacity WLL, with one sling, basket, angle β 45°- 60° kg	Width approx. under load mm	Thickness approx. under load mm	Shortest possible length mm
RSD-01000	violet	1000	800	2000	1400	1000	52	5	500
RSD-02000	green	2000	1600	4000	2800	2000	57	6	500
RSD-03000	yellow	3000	2400	6000	4200	3000	71	9	500
RSD-04000	grey	4000	3200	8000	5600	4000	76	9	500