



RSG Round sling assembly single legged

EN 1492-2 with high tensile forgings EN 1677.

Technical data RSG single legged

Model	Capacity WLL straight pull kg
RSG-01000-1-SIKA	1000
RSG-02000-1-SIKA	2000
RSG-03000-1-SIKA	3000
RSG-04000-1-SIKA	4000
RSG-05000-1-SIKA	5000



RSG Round sling assembly double legged

EN 1492-2 with high tensile forgings EN 1677.

Technical data RSG double legged

Model	Capacity WLL, straight angle β 0° - 45° kg	Capacity WLL, straight angle β 45° - 60° kg
RSG-01000-2-SIKA	1400	1000
RSG-02000-2-SIKA	2800	2000
RSG-03000-2-SIKA	4200	3000
RSG-04000-2-SIKA	5600	4000
RSG-05000-2-SIKA	7000	5000

INFO

Standard length 1-3 m. Attention: The mentioned lengths refer to the useable length L1 of the round sling.

RSG Round sling assembly three legged

EN 1492-2 with high tensile forgings EN 1677.

Technical data RSG three legged

Model	Capacity WLL, straight angle β 0°- 45° kg	Capacity WLL, straight angle β 45°- 60° kg
RSG-01000-3-SIKA	2100	1500
RSG-02000-3-SIKA	4200	3000
RSG-03000-3-SIKA	6300	4500
RSG-04000-3-SIKA	8400	6000
RSG-05000-3-SIKA	10500	7500



RSG Round sling assembly four legged

EN 1492-2 with high tensile forgings EN 1677.

Technical data RSG four legged

Model	Capacity WLL, straight angle β 0°- 45° kg	Capacity WLL, straight angle β 45°- 60° kg
RSG-01000-4-SIKA	2100	1500
RSG-02000-4-SIKA	4200	3000
RSG-03000-4-SIKA	6300	4500
RSG-04000-4-SIKA	8400	6000
RSG-05000-4-SIKA	10500	7500



INFO

Other lengths and capacities upon request.