



TTT Girder grab for horizontal transport

Capacity 750 - 4500 kg

The girder grab TTT is used for the horizontal transport of steel girders. Due to the split fixed jaw, it can be positioned centrally on the end of the beam. The grab should only be used in pairs.

The safety lock with positive spring tension holds the grab in position on the end of the girder even without load tension.

The lever is used to engage and disengage the jaw and to keep it open.

INFO

The angle from the vertical must not exceed 30°!

Technical data TTT

| Model | Art.-No. | Capacity kg | Jaw capacity mm | Weight kg |
|----------|-----------|-------------|-----------------|-----------|
| TTT 0,75 | N54509121 | 750 | 0 - 20 | 3 |
| TTT 1,5 | N54509122 | 1500 | 0 - 35 | 6 |
| TTT 3,0 | N54509123 | 3000 | 0 - 40 | 10 |
| TTT 4,5 | N54509124 | 4500 | 0 - 45 | 16 |

Dimensions TTT

| Model | TTT 0,75 | TTT 1,5 | TTT 3,0 | TTT 4,5 |
|---------|----------|---------|---------|---------|
| A, mm | 30 | 38 | 50 | 60 |
| B, mm | 70 | 70 | 75 | 90 |
| C, mm | 100 | 155 | 195 | 222 |
| D, mm | 142 | 150 | 195 | 222 |
| Ø E, mm | 50 | 70 | 80 | 90 |
| F, mm | 16 | 19 | 19 | 22 |
| G, mm | 16 | 20 | 25 | 30 |
| H, mm | 225 | 335 | 400 | 450 |
| I, mm | 45 | 45 | 80 | 90 |
| J, mm | 200 | 210 | 214 | 248 |
| K, mm | 106 | 120 | 125 | 147 |
| L, mm | 52 | 66 | 80 | 88 |

