Test mode

Torque mode

XE1*power*

FULLY AUTOMATIC WITH THE PUSH OF A BUTTON

The XE1*power* sets new standards in hydraulic bolting technology. The fully automatic system enables fast and precise bolting results with the push of a button. The work process is greatly simplified by the automatic switch-off once the final torque is reached. This innovative power pack combines efficiency, precision and convenience for demanding bolting applications.

Upgradeable to the *docu* and *control* model variants, the XE1*power* is the entry point to the smart pump generation.






1 PERFORMANCE
High fastening speeds with the optional 2-stage version

2 COMFORT
Fully automatic bolting allows for comfortable handling up to the preset hydraulic pressure

3 INFORMATION
Remote control with colour display: important operating parameters always in view (pressure, status message, motor/oil temperature, operating hours, power consumption and much more)





MODELS // DATA

Typ *Type*	Betriebsart *Operation mode*	max. Betriebsdruck *Pressure max.*		max. Durchfluss *flow max.*		max. Durchfluss *flow max.* (2-Stage Upgrade)		Motorleistung *Motor power*		Maße (L1 x B1 x H1) *Dimensions (L1 x B1 x H1)*	Gewicht* *Weight**	
		bar	psi	l/min	gal/min	l/min	gal/min	kW	hp		kg	lbs
XE1*power* 10	Automatik *automatic*	800	11,600	0,8	0.21	5,4	1.43	0,8	1.07	455 x 286 x 449 mm 17.91 x 11.26 x 17.68 in	24	52.9
XE1*power* 20	Automatik *automatic*	800	11,600	1,2	0.32	8,0	2.11	1,1	1.48	500 x 343 x 465 mm 19.69 x 13.50 x 18.31 in	34	75.0
XE1*power* 30	Automatik *automatic*	800	11,600	3,0	0.79	13,2	3.49	2,2	2.95	500 x 343 x 465 mm 19.69 x 13.50 x 18.31 in	36	79.4

Repeat accuracy: ≤ 4%, depending on the bolted joint. Technical data without guarantee.
Units available in the following voltages: 110V 50Hz, 110V 60Hz, 230V 50Hz, 230V 60Hz, 400V 50Hz, 400V 60Hz. Others on request.