

Handheld Screwdriver pneumatic



MICROMAT Screwdrivers

The basic solution for almost all screwdriving tasks

straight design - torque from 0.02 to 0.7 Nm (3 to 97 in.oz)



- robust
- completely accurate
- ergonomic, long life, quiet

The particular strength of the MICROMAT screwdriver - scarcely larger than a pen - is that it can carry out screw assemblies with torque ranges from 2 Ncm to 70 Ncm.

The slim MICROMAT screwdriver is extremely durable. This is ensured by its specific design for heavy industrial use and its extraordinary processing quality. The ergonomic design of the handle guarantees ease of use during continuous operation.

Torque accuracies of < 3% standard deviation and thus Cmk values of ≥ 1.67 with a tolerance of $\pm 15\%$ can be reached * with MICROMAT handheld screwdrivers. Statistically speaking, the error rate is less than 0.6 per one million screw assemblies.

*) under suitable process conditions

Technical data		Motor Size 0				Motor Size 0 with seek-function*)
Screwdriver right-rotation, right shut-off Push-To-Start	Type Part no.	345-308 339267A	345-408 345763A	345-708 385162A	345-508 339268A	345-508-2 341337B
Screwdriver In combination with feeder	Type Part no.	345Z-308 338053A	345Z-408 338053E	345Z-708 338053G	345Z-508 338053B	- -
Screws	up to	M3	M3	M3	M3	M3
Torque	min.	Ncm/in.oz	2/2.84	2/2.84	2/2.84	2/2.84
	soft pull-up	max.	Ncm/in.oz	50/71	55/78.1	70/99.4
	hard pull-up	max.	Ncm/in.oz	60/85.2	55/78.1	70/99.4
Speed, idling		rpm	1600	1100	600	350
Air consumption		m ³ /min/cfm	0.1/3.5	0.1/3.5	0.1/3.5	0.1/3.5
Main body dia.		mm/in.	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆
Length / length version "Z"		mm/in.	152/6 / 123/4 ²⁷ / ₃₂		158/6 ⁷ / ₃₂ / 130/5 ¹ / ₈	
Weight		kg/lbs	0.15/0.33	0.15/0.33	0.16/0.35	0.16/0.35
Noise level		dB(A)	65	65	65	65
Air hose dia.		mm/in.	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈
Hose dia. for screw suction		mm/in.	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈
Internal hex. drive DIN ISO 1173			B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")
Suitable tool inserts and connecting components with a drive as per DIN ISO 1173			A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")
Quick change chuck, mounted			yes	yes	yes	yes
Screwdriver reversible, right shut-off Push-To-Start	Type Part no.	345-308U 339269A	345-408U 345764A	345-708U 385163B	345-508U 339270A	345-508U2 341124B
Screws	up to	M3	M3	M3	M3	M3
Torque	min.	Ncm/in.oz	2/2.84	2/2.84	2/2.84	2/2.84
	soft pull-up	max.	Ncm/in.oz	40/56.8	50/71	70/99.4
	hard pull-up	max.	Ncm/in.oz	50/71	50/71	70/99.4
Speed, idling		rpm	1300	950	480	300
Air consumption		m ³ /min/cfm	0.1/3.5	0.1/3.5	0.1/3.5	0.1/3.5
Main body dia.		mm/in.	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆
Length		mm/in.	167/6 ⁹ / ₁₆	167/6 ⁹ / ₁₆	173/6 ¹³ / ₁₆	173/6 ¹³ / ₁₆
Weight		kg/lbs	0.17/0.38	0.17/0.38	0.18/0.40	0.18/0.40
Noise level		dB(A)	65	65	65	65
Air hose dia.		mm/in.	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈
Hose dia. for screw suction		mm/in.	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈
Drive hex. female			3 mm/.118"	3 mm/.118"	3 mm/.118"	3 mm/.118"
Internal hex. drive DIN ISO 1173			B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")
Suitable tool inserts and connecting components with a drive as per DIN ISO 1173			A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")
Quick change chuck, mounted			yes	yes	yes	yes
Included in delivery:	Hose coupling with nozzle, nipple (mounted) · Torque adjustment tool · Assortment of clutch springs					
Optional equipment						
Exhaust hose (1m/3.28ft.)	Part no.	806113				
Spring sleeve cpl. (in connection with finder, see catalog: inserting tools D3320E)	Part no.	364670A				
Foam rubber grip	Part no.	833058				

Performance data relate to an air pressure of 6.3 bar (90 PSI)

▶ Please also find tool inserts in our catalog D3320E.	▶ *) For ornamental screws with a scratch sensitive surface, we recommend the use of our MICROMAT screwdrivers with an integrated seek-function. This option allows the bit to engage with the screw drive at a lowered speed. Once full down-pressure is applied, the screw is then assembled with the rated full speed. For this screwdriver type we recommend a possibility of interruption of air supply.	▶ Details on our feeding systems can be found in catalog D3820E.
--	---	--

DEPRAG

DEPRAG SCHULZ GMBH u. CO. KG
P.O. Box 1352 | D-92203 Amberg
Carl-Schulz-Platz 1 | D-92224 Amberg
Phone: +49 9621 371-0 | Fax: +49 9621 371-120
www.deprag.com | info@deprag.de

CERTIFIED AS PER DIN EN ISO 9001